



## TECHNICAL SPECIFICATION SHEET

Range

**Osaka DWR**

Design

Flat woven chenille

Composition  $\pm 3\%$  per Compound

100% Polyester

Useable Fabric Width (cm)

138cm

Pattern Repeat (cm)

|          |     |            |     |
|----------|-----|------------|-----|
| Vertical | n/a | Horizontal | n/a |
|----------|-----|------------|-----|

Martindale (rubs)

$\geq 35,000$

Seam (mm)

|      |    |      |    |
|------|----|------|----|
| Warp | >1 | Weft | >1 |
|------|----|------|----|

Tensile (N)

|      |       |      |            |
|------|-------|------|------------|
| Warp | >1000 | Weft | $\geq 650$ |
|------|-------|------|------------|

Tear (N)

|      |      |      |     |
|------|------|------|-----|
| Warp | >100 | Weft | >40 |
|------|------|------|-----|

Pilling Grade

|             |   |             |   |
|-------------|---|-------------|---|
| @ 2000 rubs | 4 | @ 5000 rubs | 4 |
|-------------|---|-------------|---|

Bursting (kPa)

n/a

Weight (gsm)  $\pm 5\%$

420

FR Weight (gsm)  $\pm 5\%$

|    |     |           |     |
|----|-----|-----------|-----|
| UK | n/a | SIAN SWHF | 540 |
|----|-----|-----------|-----|

Care Instructions

|           |     |
|-----------|-----|
| WV FINISH | 610 |
|-----------|-----|

Spot clean in situ

